



- A** 56" Max 42" Min
- B** Roof must mount in front of Halo Bar. MUST be same on both sides.
- C** Roof MUST be flat or curve downward. Max 6" rake front to back.
- D** 42" Max.
- E** 112" Max 108" Min.
- F** 48" Max 34" Min.
- G** 2" Ground Clearance.
- H** Hood 6" Max on sides.
- I** 20" Max 16" Min Ground to center of bumper. (Bumper not mandatory outside of nose)
- J** 34" Max 28" Min (including skirt)
- K** 72" Max, 4" tolerance.
- L** 20" Max 12" Min. (Both sides)
- M** Doors may be dished. 3" Max clearance.
- N** 120" Max 106" Min.
- O** Max 4" bow from roof to decking. Can be solid or open. (Same both sides)
- P** 4" Max from decking to farthest point.
- Q** Interior slope is 6" MAX, front to rear. Must be flat across at rear. MUST be same angle FRONT to BACK. 1" tolerance. Decking must be flat and flush with body.
- R** 39" MAX. 0 tolerance.
- S** 45" Max, Nose must be flat across.
- T** 40" Max at front, 68" Max at back.
- U** 54" Max 44" Min.
- V** 56" Max 41" Min.
- W** Left side MUST be straight front to back. 1" tolerance.
- X** 68" Max at rear 62" Min at front. 74" Max at widest point on body.
- Y** Sail panels must slope down from rear of roof to rear of decking. 2" curve at center. Must mount within 2" of outside edge of decking.
- Z** 2" Max.